

80CH-EVO

**Pioneer Prime Vacuum Assisted
Stage V Diesel-Driven Centrifugal Pump
Sound Attenuated Canopy Package**

Pump Specifications

Model	PP63C17
Size	6 x 3" (150 x 80 mm)
Max Flow	245 m ³ /h
Max Head	116 m
Solids Size	0.75" (19 mm)



Engine Specifications

Engine Type	Perkins 904J-E36TA, Diesel
Displacement	3.6 l
Fuel Consumption at BEP	17.5 l/h @ 1900 rpm
Max Running Hours at BEP	40 h @ 1900 rpm
Continuous Power	121 HP (90 kW) @ 1900 rpm
Aftertreatment Specifics (DEF, DOC, SCR, etc.)	Diesel Particulate Filter, Diesel Oxidation Catalyst, Selective Catalytic Reduction
Emmissions Compliance	EU Stage V

Priming System

Priming System	Mechanically Driven Vacuum Pump
Air Removal Capacity	24 l/s (50CFM)
Priming Chamber	Air Separation Pioneer Prime w/SS Components
Discharge Check Valve	Ductile Iron Body; Swing Flex Nitrile Rubber Flapper
Run Dry System	Oil Reservoir for Mechan- ical Seal; Indefinite Run-Dry Capability

Features

- Indefinite Run-Dry Capability
- Environmentally Safe Priming System with Patented PosiValve™
- Spark Arresting Silencer
- Auxiliary Fuel Tank Connections
- Digital Fuel Level Gauge
- Digital Suction & Discharge Pressure Transducers

Options and Accessories

Telemetry	Full Control & Remote Monitoring with Alerts
Certified Spark Arrestor	ATEX Approved
Trailers	EU Approved, Fast Tow or Plant Trailers & Heavy Duty Non-EU Site Tow Trailer
Safety	Air Intake Shutdown Valve
Battery Standby	Solar Panel Trickle Charger
Materials	Duplex Stainless Steel Available


Package Specifications

Fuel Tank Capacity	695 l
Control Panel	E400 Auto Stop/Start
Operating Speed (Min. /Max.)	1400 - 1900 rpm
Weight (Dry / Wet)	2555 kg / 3100 kg
Dimensions (L × W × H)	2982 × 1447 × 2103 mm
Enclosure dB(A) Rating	70 dB(A) @ 7m
Canopy Material & Finish	Steel, Painted RAL6005
Skid/Bund Material & Finish	Carbon Steel, Hot Dip Galvanised

Materials of Construction

Impeller	CA6NM Stainless Steel
Shaft	17-4 PH Stainless Steel
Wear Ring	ASTM A48 Class 40 Gray Iron
Volute	Ductile Iron ASTM A536 65-45-12
Mechanical Seal	Silicon Carbide Rotating vs Tungsten Carbide Stationary, Fluoroelastomers

Mechanical Dimensions & Weights



Weight (Dry / Wet): 2555 kg / 3100 kg

Performance Curve

Model: PP63C17

Impeller Diameter: 17"

Solids Size: 0.75"

